

PIŁA TARCZOWA WIELOPIŁY - 4SS302502

Model: M3 CE

SECOND-HAND MULTIRIP SAW SCM MOD. M3

MULTIRIP SAW SCM MOD. M3 - CE RULES

- Year of manufacture: 2001
- Serial number: AB145642
- Power supply voltage: 400 V / 50 Hz
- Motor power: 18.5 kW
- Blade rotation speed: 4,200 rpm
- Maximum blade pack width: 300 mm
- Conveyor belt width: 300 mm
- Maximum blade diameter: 350 mm
- Minimum blade diameter: 200 mm
- Minimum workpiece length: 390 mm
- Blade bore diameter (shaft): 70 mm
- Keyway dimensions on blade shaft: 20 x 5 mm
- Distance from machine base to first right blade: 200 mm
- Conveyor feed speed: continuously adjustable from 6 to 48 m/min
- Conveyor type: with direct-joint spheroidal cast iron pads
- Conveyor guide rails: low-friction, one with prismatic profile for perfect straightness
- Conveyor lubrication: automatic
- Clutch: present on feed speed variator
- Working table height from floor: 750 mm
- Working table dimensions: 1,530 x 950 mm
- Dust extraction port for blades: Ø 200 mm
- Dust extraction port for conveyor: Ø 120 mm
- Air volume extracted (at 25 m/sec): 3,850 m³/h
- Programmable fence: with turret stops, pneumatic positioning via foot pedal
- Laser reference: for cutting line
- Base frame: made of single-block cast iron





Caselli Group SPA
Via Nazionale, 87
33048 - San Giovanni al Natisone
Udine - Italia
Tel: +39 0432 757 064
Web: www.casellispa.com
Email: info@casellispa.com
