

FERĂSTRĂU CIRCULAR CU CAR SCURT - 4SS202507

Model:

BAND SAWS FOR THIN CUTTING WITH MAXIMUM PRECISION CENTAURO MOD. SUPERCUT 80

BAND SAWS FOR THIN CUTTING WITH MAXIMUM PRECISION CENTAURO MOD. SUPERCUT 80

- Thin layer from 2 mm thickness
- Maximum cutting accuracy up to ± 0.15 mm
- Minimal kerf, cutting thickness from 1.3 mm
- Ideal for the cutting of dried and wet wood or alternative materials
- Surface of the thin layer ready for gluing without need of further processing steps
- Ground table
- 6 rubber idler rollers adjustable in height, for opening/closing to ensure the best pneumatic pressure on the workpiece during feeding and cutting
- Oleo-pneumatic tensioning of the blade for better cutting performance
- Top and bottom "Chaco" blade-guides which guarantee the best stability blade during cutting
- Internal/external lubrication of the blade to remove residues of resins and chips
- 4 dust extraction to optimize the suction of dust and chips
- Cutting height of 400 mm
- Cutting width up to 400 mm
- High quality powerful motor kW 15
- Carbide or stellite blades for best cutting performance
- Easy maintenance
- CE rules
- Year 2011



